

Please amend the Abstract at page 13 as follows:

~~Disclosed is a~~ A micro mode executing apparatus of a digital still camera ~~using a focus driving motor, in which~~ has an image sensor and a focus controlling lens ~~are~~ connected to a focus driving motor and a spindle of the motor, thereby controlling an optical length within a the range of ~~not changing~~ a fixed barrel structure. The micro mode executing apparatus ~~comprises~~ a motor that moves ~~transferred~~ along a rotating axis of a the spindle with a rotating direction of the motor being changed in line accordance with an applied electrical signal ~~with reference to the rotating axis of the spindle;~~ a An image sensor, is mounted integrally onto one side of the motor through a fixing member, ~~for converting~~ and acts to convert an image of an object to an electrical signal. ~~;~~ a A focus lens is positioned on a the same optical axis as the image sensor and is secured to one end of the rotating axis of the spindle; ~~;~~ a A housing consisting of a first step region for limiting a transferring area of the motor and a second step region for limiting a transferring area of the focus lens, wherein the first and second step regions forming form a barrel structure having a step layer; ~~;~~ a A first biasing member is connected to the focus lens and the motor, and ~~having~~ has a constant biasing force; and a second biasing member is provided for positioning the motor on the first step region ~~by~~ for applying a biasing force ~~to~~ in a lateral direction.